



# Tilt-A-Dor®



The B&D range of Tilt-A-Dor® fittings offer the opportunity to create a door that is harmonic with its surroundings, giving the building a truly unique appearance. With durability and safety being primary concerns, Tilt-A-Dor fittings offer the always exceptional B&D quality, providing you with the opportunity to design a door only limited by your imagination.§

STRONG & DURABLE

ANTI SWAY BRACKFT

SULLS FOR HEADROOM

TAILOR YOUR DOOR

SUITS LARGE DOORS



Call 13 62 63 or visit www.bnd.com.au for further information

### TRACK FITTINGS

Perfectly suited to larger doors where greater stability is provided through the addition of horizontal tracks to hold the door in the open position so as to minimise protrusion outside the opening.

### **JAMB FITTINGS**

An economical solution for use in applications where there is limited headroom and sideroom. Fittings are zinc plated for greater resistance to corrosion.

# **TILT FITTINGS FEATURES**

 New spring restraint feature to ensure that spring movement is contained, and eliminates the possibility of spring separation from the fitting.

- Powder coated fittings offer greater durability, strength and resistance to corrosion.
- Springs designed to provide optimum performance throughout the working life of the fittings.
- Minimal installation clearances required giving the fittings and jamb the ability to fit where some other garage doors will not.
- Supplied with weatherstrip for fitting to the door panel to help restrict entry of water and leaves
- Strengthened bearing design for greater durability over the life of the fittings.
- Robust anti-sway bracket to limit the degree of lateral movement.
- Available in a number of configurations to suit both single and double width openings.


TRACK FITTINGS					
	70 <b>–</b> T	100-T	120-T	175–T	
Maximum Door Weight	70kg	100kg	120kg	175kg	
Minimum Door Height	1850mm	1850mm	1900mm	1900mm	
Maximum Door Height	2250mm	2250mm	2400mm	2700mm	
Finish	Zinc plated	Zinc plated	Zinc plated	Zinc plated	
Spring Restraint Feature	Yes	Yes	Yes	Yes	
Number of springs	2	2	4	4	
Spring life (Cycles)	20,000	20,000	20,000	20,000	
Weatherstrip	Yes	Yes	Yes	Yes	
Headroom (Manually operated doors / With automatic opener)	50mm / 100mm	50mm / 100mm	50mm / 100mm	50mm / 100mm	
Sideroom	70mm	70mm	70mm	90mm	

JAMB FITTINGS					
	70J	70J SIDE FIX	90J		
Maximum Weight	70kg	70kg	90kg		
Minimum Height	1850mm	1850mm	1850mm		
Maximum Height	2250mm	2250mm	2250mm		
Finish	Zinc plated	Zinc plated	Zinc plated		
Spring Restraint Feature	Yes	Yes	Yes		
Spring life (Cycles)	20,000	20,000	20,000		
Weatherseal	No	No	No		
Headroom (Depends on mounting hole used)	20 - 150mm	20 - 150mm	20 - 150mm		
Sideroom	50mm	Omm	50mm		

Use of the mounting hole number 2 and 3 is not recommended for doors that are to be automated with an electric opener.

Before proceeding please check the opening measurements against the panel and ensure that the correct fitting has been obtained in regards to door weight.

#### Door overlap lintel (Jamb type)^



INSTALLATION CLEARANCES					
	TRACK FITTINGS	JAMB FITTINGS (DOOR UNDER LINTEL)			
Door Width	Opening Width – 20mm	Opening Width – 24mm			
Door Height	Opening Height – 27mm	Opening Height – 24mm			
Headroom	50mm for a manually operated door 100mm with an automatic opener	25mm for a manually operated door 200mm with an automatic opener using hole number 1 only			
Х	15mm	12mm			

<sup>^</sup>Optional Jamb fitting installation

# YOUR **B&D REPRESENTATIVE** IS:

International Customers call +61 2 9722 5555



c) Prefixed Trademarks are trademarks of B&D Australia Pty Ltd.

B&D Doors has offices servicing all states. For more details on this product or our other ranges, call **13 62 63** or visit **www.bnd.com.au** 

- a) For areas within one kilometre of a corrosive environment e.g. salt air or industrial fallout, special care and maintenance are generally required for metal products. Consult B&D or your B&D Accredited Dealer for advice.
- b) The company reserves the right to make changes or improvements to the products or accessories without notice and without incurring any obligation to make similar changes or improvements to goods previously ordered. Specifications subject to change without notice.
- d) B&D products have many patents and registered designs applicable.
- e) Details correct at date of publication.
- f) § Please note that B&D provide the tilt door fittings only, not the actual door panel.
- g) † Tilt-A-Dor® fittings, in normal residential use are covered by a two year warranty for all components and labour conditional on care and servicing as recommended in the door's handbook. Full details of the warranty are available, on request, from your nearest B&D office.

,

